

# CLUB 512

## USB to DMX interface



**FREE SOFTWARE & APPLICATION DOWNLOAD**

Our professional package for entry-level budgets and users seeking an easy-to-operate DMX control system.

Newly designed aluminium housing with beautiful finish and updated electronics that work with all the latest 2022 Chromateq software (as well as older versions of LED Player and Pro DMX).

Capable of 3 trigger options and equipped with DC 5-18V input this USB to DMX controller includes an infrared remote control and USB 5V power supply in the package.

It is the perfect hardware for easy integration projects.

CLUB 512 XLR



CLUB 512 TB



## HARDWARE Features

|                                               |                                                                                                                                                                                                                                                      |
|-----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DMX output                                    | 512 In/Out channels PC and 512 Out Stand Alone                                                                                                                                                                                                       |
| Input                                         | USB-C (5V. DC, 0.1A)                                                                                                                                                                                                                                 |
| Zone                                          | 1 Zone, play 1 scene/sequence at time in Stand Alone                                                                                                                                                                                                 |
| Memory                                        | Internal memory (200 KB, 200 to 2000 DMX step capacity)                                                                                                                                                                                              |
| Infrared (scenes, play, pause, dimmer, speed) | Additional Infrared commands and additional commands on triggers                                                                                                                                                                                     |
| DMX Modes                                     | DMX In/Out, DMX Record, DMX Trigger                                                                                                                                                                                                                  |
| Stand Alone Options                           | 16-bit and fine channel management<br>Cross Fade time between scenes<br>Default start scene when power up                                                                                                                                            |
| Triggers                                      | 3 Triggers, Contact on external T. Block<br>(On, On/Off, Release, Restart, Scene, Commands and function Controls, Priority)<br>Infrared receiver (Remote control included)<br>Infrared options: 15 scene selection, speed, dimmer, pause, stop, next |
| Max DMX outputs (USB)                         | x12 USB interfaces connected = 12 DMX max                                                                                                                                                                                                            |
| Power                                         | DC In USB-C 5V DC + 5-18V DC Input on Terminal Block                                                                                                                                                                                                 |
| Dimensions (mm / in)                          | H: 55 (2.16), W: 50 (1.96), D: 37.5 (1.47)                                                                                                                                                                                                           |
| Weight                                        | 0.85 Kg (1.87 lb)                                                                                                                                                                                                                                    |
| Housing                                       | Extruded Aluminum                                                                                                                                                                                                                                    |
| I/O Connectors                                | USB-C 2.0, 3 pin XLR (XLR5 optional), 6 pin T. BLock                                                                                                                                                                                                 |
| Operating Temperature                         | -40 to +85 C°                                                                                                                                                                                                                                        |
| IP Rating                                     | IP40                                                                                                                                                                                                                                                 |
| Certifications                                | CE, LVD, RoHS                                                                                                                                                                                                                                        |
| International Warranty                        | 3 year                                                                                                                                                                                                                                               |



## SOFTWARE Features

|                             |                                                   |
|-----------------------------|---------------------------------------------------|
| PRO DMX 2                   | Yes, up 64x512 DMX output max                     |
| PIXXEM                      | No                                                |
| LED PLAYER                  | Yes, up 64x512 DMX output max                     |
| PRO DMX                     | Yes, No Audio and Video Timeline                  |
| STUDIO DMX                  | Yes, 3D viewer in real time (Full mode)           |
| WI-LIGHT 2 - APP            | Yes, Software LAN control from PC, Tablet, Mobile |
| Art-Net Output from PC      | 1x512 DMX Outputs per connected device            |
| System Compatibility        | Windows, iOS, Linux, Raspberry                    |
| Worldwide Technical Support | Yes, English, French, Spanish, Chinese            |

### Mobile minimum configuration :

Android 5 / iOS 10 and +  
1Ghz CPU, 1 Gb RAM, 60 Mb disk

### Configuration minimale PC :

Windows, Mac OS, Linux (32 and 64 bits)  
2Ghz CPU (2 cores), 8 Gb RAM  
2Gb RAM graphic card (for 3D only)  
600 Mb disk, 1920x1080 resolution  
1 USB port (Device)  
1 Ethernet Port (for Art-Net & sACN)